

CORRECTED VERSION

07 JUL 2004

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
17 July 2003 (17.07.2003)

PCT

(10) International Publication Number  
**WO 03/058844 A1**

(51) International Patent Classification<sup>7</sup>: **H04B 7/08**

(21) International Application Number: PCT/EP02/00277

(22) International Filing Date: 9 January 2002 (09.01.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **NOKIA CORPORATION** [FI/FI]; Keilalahdentie, FIN-02150 Espoo (FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **KOKKONEN, Mikko** [FI/FI]; Limingantie 50 B 8, FIN-00560 Helsinki (FI).

(74) Agents: **PAGE WHITE & FARRER** et al.; 54 Doughty Street, London WC1N 2LS (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,

LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

(48) Date of publication of this corrected version:

28 August 2003

(15) Information about Correction:

see PCT Gazette No. 35/2003 of 28 August 2003, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND RECEIVER FOR RECEPTION OF A COMPOSITE SIGNAL

(57) Abstract: A receiver for receiving a plurality of signals at the same time, said receiver comprising: a plurality of receiving elements each of which is arranged to receive a composite signal including at least some of said plurality of signals; processing means for providing a estimate of at least two of said plurality of signals, said processing means being arranged to provide an estimate of a first one of said signals and then to provide an estimate of a second one of said signals, wherein said estimate of said second one of said signals takes into account the estimate of the first signal and the estimate of the first signal can be modified in dependence on the estimate of the second signal.

WO 03/058844 A1